

2020 Kansas Statutes

8-1909. Gross weight limits for vehicles; exceptions; safety of certain vehicles for operation.

(a) No vehicle or combination of vehicles shall be moved or operated on any highway when the gross weight on two or more consecutive axles exceeds the limitations prescribed in the following table:

Distance in feet between the extremes of any group of 2 or more consecutive axles	Maximum load in pounds carried on any group of 2 or more consecutive axles							
	2 axles	3 axles	4 axles	5 axles	6 axles	7 axles	8 axles	
4	34,000							
5	34,000							
6	34,000							
7	34,000							
8 and less	34,000	34,000						
More than 8	38,000	42,000						
9	39,000	42,500						
10	40,000	43,500						
11	44,000							
12	45,000	50,000						
13	45,500	50,500						
14	46,500	51,500						
15	47,000	52,000						
16	48,000	52,500	58,000					
17	48,500	53,500	58,500					
18	49,500	54,000	59,000					
19	50,000	54,500	60,000					
20	51,000	55,500	60,500	66,000				
21	51,500	56,000	61,000	66,500				
22	52,500	56,500	61,500	67,000				
23	53,000	57,500	62,500	68,000				
24	54,000	58,000	63,000	68,500	74,000			
25	54,500	58,500	63,500	69,000	74,500			
26	55,500	59,500	64,000	69,500	75,000			
27	56,000	60,000	65,000	70,000	75,500			
28	57,000	60,500	65,500	71,000	76,500	82,000		
29	57,500	61,500	66,000	71,500	77,000	82,500		
30	58,500	62,000	66,500	72,000	77,500	83,000		
31	59,000	62,500	67,500	72,500	78,000	83,500		
32	60,000	63,500	68,000	73,000	78,500	84,500		
33	64,000	68,500	74,000	79,000	85,000			
34	64,500	69,000	74,500	80,000	85,500			
35	65,500	70,000	75,000	80,500				
36	66,000	70,500	75,500	81,000				
37	66,500	71,000	76,000	81,500				
38	67,500	72,000	77,000	82,000				
39	68,000	72,500	77,500	82,500				
40	68,500	73,000	78,000	83,500				
41	69,500	73,500	78,500	84,000				
42	70,000	74,000	79,000	84,500				
43	70,500	75,000	80,000	85,000				

44	71,500	75,500	80,500	85,500
45	72,000	76,000	81,000	
46	72,500	76,500	81,500	
47	73,500	77,500	82,000	
48	74,000	78,000	83,000	
49	74,500	78,500	83,500	
50	75,500	79,000	84,000	
51	76,000	80,000	84,500	
52	76,500	80,500	85,000	
53	77,500	81,000	85,500	
54	78,000	81,500		
55	78,500	82,500		
56	79,500	83,000		
57	80,000	83,500		
58	84,000			
59	85,000			
60	85,500			

except that two consecutive sets of tandem axles may carry a gross load of 34,000 pounds each if the overall distance between the first and last axles is 36 feet or more.

(1) The gross weight on any one axle of a vehicle shall not exceed the limits prescribed in K.S.A. 8-1908, and amendments thereto.

(2) Except as otherwise provided by subsection (e), for vehicles and combinations of vehicles on the interstate system the table in this section shall not authorize a maximum gross weight of more than 80,000 pounds.

(3) The table in this section shall not apply to truck tractor and dump semitrailer or truck trailer combination when such are used as a combination unit exclusively for the transportation of sand, salt for highway maintenance operations, gravel, slag stone, limestone, crushed stone, cinders, coal, blacktop, dirt or fill material, when such vehicles are used for transportation to a construction site, highway maintenance or construction project or other storage facility, except that such vehicles or combination of vehicles shall not be exempted from any application of the table as may be required to determine applicable axle weights for triple and quad axles as defined in K.S.A. 8-1908, and amendments thereto. As used in this paragraph (3), the term "dump semitrailer" means any semitrailer designed in such a way as to divest itself of the load carried thereon.

(b) Any vehicle registered under the laws of this state which vehicle is designed and used primarily for the transportation of property or for the transportation of 10 or more persons may, at the time of its registration, be subjected by the director of vehicles to investigation or test as may be necessary to enable such director to determine whether such vehicle may safely be operated upon the highways in compliance with all provisions of this act. Every such vehicle shall meet the following requirements:

(1) It shall be equipped with brakes as required in K.S.A. 8-1734, and amendments thereto.

(2) Every motor vehicle to be operated outside of business and residence districts shall have motive power adequate to propel such vehicle and any load thereon or to be drawn thereby, at a speed which will not impede or block the normal and reasonable movement of traffic. Exception to this requirement shall be recognized when reduced speed is necessary for safe operation or when a vehicle or combination of vehicles is necessarily or in compliance with law or police direction proceeding at reduced speed.

(c) It shall be unlawful for any person to operate any vehicle or combination of vehicles with a gross weight in excess of the limitations set forth in article 19 of chapter 8 of [the] Kansas Statutes Annotated, and amendments thereto, except as provided in K.S.A. 8-1911, and amendments thereto.

(d) As used in this section, "interstate system" means the national system of interstate and defense highways.

(e) A vehicle, if operated by an engine fueled primarily by natural gas, may exceed any vehicle weight limit under this section, up to a maximum gross vehicle weight of

82,000 pounds, by an amount that is equal to the difference between:

- (1) The weight of the vehicle attributable to the natural gas tank and fueling system carried by that vehicle; and
- (2) the weight of a comparable diesel tank and fueling system.

History: L. 1974, ch. 33, § 8-1909; L. 1975, ch. 427, § 48; L. 1980, ch. 45, § 1; L. 1981, ch. 46, § 3; L. 1983, ch. 41, § 4; L. 1986, ch. 45, § 2; L. 2016, ch. 44, § 3; Apr. 14.